

Program LEQ Professional v. 6-2019 dla Windows

Projekt:

Z:\Prosiaczek\11.03.2020\kompleks budynków\dzień 4m.dat

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0.900

Temperatura otoczenia 10[°C]

•ródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
=====					
1	839.3	363.4	1.4	89.4	B1E1
2	840.7	368.8	5.0	69.8	B1E2
3	848.0	375.5	5.0	69.8	B1E3
4	849.4	384.4	5.0	69.8	B1E4
5	857.0	392.0	5.0	69.8	B1E5
6	859.8	401.2	5.0	69.8	B1E6
7	871.0	412.4	5.0	69.8	B1E7
8	869.6	422.0	5.0	69.8	B1E8
9	877.4	422.8	5.0	69.8	B1E9
10	876.6	433.2	5.0	69.8	B1E10
11	885.5	436.0	5.0	69.8	B1E11
12	883.3	430.4	5.0	64.9	B1E12
13	864.8	458.1	6.0	75.0	B2E1
14	860.6	459.8	6.0	75.0	B2E2
15	857.2	461.7	6.0	75.0	B2E3
16	818.9	380.2	6.0	75.0	B2E4
17	815.8	382.8	6.0	75.0	B2E5
18	812.2	384.4	6.0	75.0	B2E6
19	785.6	376.0	6.0	75.0	B3E1
20	782.2	378.3	6.0	75.0	B3E2
21	778.8	379.7	6.0	75.0	B3E3
22	775.8	381.6	6.0	75.0	B3E4
23	848.6	488.6	6.0	75.0	B3E5
24	846.0	490.6	6.0	75.0	B3E6
25	843.0	491.7	6.0	75.0	B3E7
26	840.2	493.6	6.0	75.0	B3E8
27	760.9	390.0	6.0	75.0	B4E1
28	757.8	392.0	6.0	75.0	B4E2
29	754.5	394.0	6.0	75.0	B4E3
30	751.7	395.4	6.0	75.0	B4E4
31	824.5	501.2	6.0	75.0	B4E5
32	821.4	503.4	6.0	75.0	B4E6
33	818.3	505.7	6.0	75.0	B4E7
34	815.5	506.8	6.0	75.0	B4E8
35	743.3	414.4	6.0	75.0	B5E1
36	739.6	416.4	6.0	75.0	B5E2
37	736.6	418.0	6.0	75.0	B5E3
38	733.5	420.0	6.0	75.0	B5E4
39	797.3	567.8	4.5	69.9	B6E1
40	689.0	380.9	1.0	69.2	A1a
41	691.8	386.3	1.0	69.2	A1b

42	807.3	552.4	1.0	72.9	A2a
43	794.7	519.8	1.0	72.9	A2b
44	838.2	505.9	1.0	72.9	A2c
45	864.0	491.8	1.0	72.9	A2d
46	833.3	352.3	1.0	72.9	A2e
47	820.1	356.9	1.0	72.9	A2f
48	710.6	398.9	1.0	72.9	A3a
49	697.3	389.8	1.0	72.9	A3b
50	781.8	519.6	1.0	71.5	A5a
51	762.7	502.7	1.0	71.5	A5b
52	682.5	392.4	1.0	64.4	A6a
53	667.4	404.8	1.0	64.4	A6b
54	885.7	403.2	1.0	74.1	A4a
55	899.8	446.7	1.0	74.1	A4b
56	876.7	489.4	1.0	74.1	A4c
57	814.6	562.7	1.0	74.1	A4d

=====

•ród³a typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŃKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	830.9	367.9	875.7	447.2	893.4	436.8	848.0	358.7	0.0	4.5
2	828.1	378.3	869.8	451.9	847.2	464.8	805.7	391.2	0.0	4.5
3	771.8	387.2	832.6	494.2	850.8	483.6	789.5	377.7	0.0	4.5
4	748.0	401.5	809.1	507.9	825.9	497.6	765.1	391.4	0.0	4.5
5	729.6	426.2	771.0	496.7	788.6	486.9	747.5	415.2	0.0	4.5
6	788.8	567.1	794.2	576.6	807.8	565.8	801.7	557.6	0.0	3.5

=====

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr Źród³a			A	63	125	250	500	1000	2000	4000	8000	wsp.odB.
1	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====

Nr Źród³a			A	63	125	250	500	1000	2000	4000	8000	wsp.odB.
=====												
2	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====												
3	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====												
4	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====												
5	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====												
6	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
----	--------	------	------	------

1	701.0	524.2	4.0
2	599.0	562.0	4.0
3	560.2	481.0	4.0
4	571.7	359.6	4.0
5	593.7	689.6	4.0
6	609.5	728.3	4.0
7	547.9	762.6	4.0
8	497.8	782.0	4.0
9	483.7	784.6	4.0
10	835.4	77.4	4.0